

Typical Applications

- Mounts inside select Tilton and QM rear-mount starter bellhousings



Features

- **Mount Type:** 3-Bolt "QM-type" pattern
- **Piston Area:** 1.215in² (784mm²)
- **Max Stroke:** .600" (15.24mm)
- **Ports:** AN3 (3/8"-24 thread)
- **Weight:** .75- .85 lbs (varies by model)

Bearing Type: Radius-face
Contact Diameter: 1.75" (44mm)

| 2200-Series | | Replacement Bearing | Replacement Piston | Seal Kit |
|-------------|----------------|---------------------|--------------------|----------|
| Part Number | Height* | | | |
| 60-2200 | 2.90" (73.7mm) | 62-031 | 62-6000 | 62-905 |
| 60-2210 | 3.00" (76.2mm) | 62-031 | 62-6001 | 62-905 |
| 60-2220 | 3.10" (78.7mm) | 62-031 | 62-6002 | 62-905 |
| 60-2230 | 3.20" (81.3mm) | 62-031 | 62-6003 | 62-905 |
| 60-2240 | 3.30" (83.8mm) | 62-031 | 62-6004 | 62-905 |
| 60-2250 | 3.40" (86.4mm) | 62-031 | 62-6005 | 62-905 |
| 60-2260 | 3.50" (88.9mm) | 62-031 | 62-6006 | 62-905 |
| 60-2270 | 3.60" (91.4mm) | 62-031 | 62-6007 | 62-905 |
| 60-2280 | 3.70" (94.0mm) | 62-031 | 62-6008 | 62-905 |
| 60-2290 | 3.80" (96.5mm) | 62-031 | 62-6009 | 62-905 |

*Height can be reduced by .050" (1.27mm) by removing the shim that is located under bearing within the piston

Bearing Type: Radius-face
Contact Diameter: 1.50" (38mm)

| 2300-Series | | Replacement Bearing | Replacement Piston | Seal Kit |
|-------------|----------------|---------------------|--------------------|----------|
| Part Number | Height* | | | |
| 60-2300 | 2.90" (73.7mm) | 62-008 | 62-6000 | 62-905 |
| 60-2310 | 3.00" (76.2mm) | 62-008 | 62-6001 | 62-905 |
| 60-2320 | 3.10" (78.7mm) | 62-008 | 62-6002 | 62-905 |
| 60-2330 | 3.20" (81.3mm) | 62-008 | 62-6003 | 62-905 |
| 60-2340 | 3.30" (83.8mm) | 62-008 | 62-6004 | 62-905 |
| 60-2350 | 3.40" (86.4mm) | 62-008 | 62-6005 | 62-905 |
| 60-2360 | 3.50" (88.9mm) | 62-008 | 62-6006 | 62-905 |
| 60-2370 | 3.60" (91.4mm) | 62-008 | 62-6007 | 62-905 |
| 60-2380 | 3.70" (94.0mm) | 62-008 | 62-6008 | 62-905 |
| 60-2390 | 3.80" (96.5mm) | 62-008 | 62-6009 | 62-905 |

*Height can be reduced by .050" (1.27mm) by removing the shim that is located under bearing within the piston

