

### Typical Applications

- Mounts inside select Tilton and Quicktime bellhousings

### Features

- **Mount Type:** Low Profile 4-Bolt Pattern
- **Piston Area:** 1.215in<sup>2</sup> (784mm<sup>2</sup>)
- **Max Stroke:** .600" (15.24mm)
- **Ports:** AN3 (3/8"-24 thread)
- **Weight:** .90 - 1.25 lbs (varies by model)



5000-Series		Bearing Type: Radius-face Contact Diameter: 2.05" (52mm)		
Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-5000	2.10" (53.3mm)	62-002	62-612	62-905



5100-Series		Bearing Type: Flat-face Contact Diameter: 1.71" - 2.83" (43.4mm - 71.9mm)		
Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-5100	1.84" (64.7mm)	62-618	62-6100	62-905



5200-Series		Bearing Type: Radius-face Contact Diameter: 1.75" (44mm)		
Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-5200	1.92" (48.8mm)	62-031	62-6000	62-905
60-5210	2.02" (51.3mm)	62-031	62-6001	62-905
60-5220	2.12" (53.8mm)	62-031	62-6002	62-905
60-5230	2.22" (56.4mm)	62-031	62-6003	62-905
60-5240	2.32" (58.9mm)	62-031	62-6004	62-905
60-5250	2.42" (61.5mm)	62-031	62-6005	62-905
60-5260	2.52" (64.0mm)	62-031	62-6006	62-905
60-5270	2.62" (66.5mm)	62-031	62-6007	62-905
60-5280	2.72" (69.1mm)	62-031	62-6008	62-905
60-5290	2.82" (71.6mm)	62-031	62-6009	62-905

\*Height can be reduced by .050" (1.27mm) by removing the shim that is located under bearing within the piston



5300-Series		Bearing Type: Radius-face Contact Diameter: 1.50" (38mm)		
Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-5300	1.92" (48.8mm)	62-008	62-6000	62-905
60-5310	2.02" (51.3mm)	62-008	62-6001	62-905
60-5320	2.12" (53.8mm)	62-008	62-6002	62-905
60-5330	2.22" (56.4mm)	62-008	62-6003	62-905
60-5340	2.32" (58.9mm)	62-008	62-6004	62-905
60-5350	2.42" (61.5mm)	62-008	62-6005	62-905
60-5360	2.52" (64.0mm)	62-008	62-6006	62-905
60-5370	2.62" (66.5mm)	62-008	62-6007	62-905
60-5380	2.72" (69.1mm)	62-008	62-6008	62-905
60-5390	2.82" (71.6mm)	62-008	62-6009	62-905

\*Height can be reduced by .050" (1.27mm) by removing the shim that is located under bearing within the piston

Installation drawing for 5000-Series HRBs is available at [www.tiltonracing.com/technical/installation-drawings](http://www.tiltonracing.com/technical/installation-drawings)

