

## Typical Applications

- Bulkhead-mounted inside transmission or bellhousing with adapter plate



### 8000-Series

Bearing Type: Radius-face  
Contact Diameter: 2.05" (52mm)

Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-8000	2.05" (52.0mm)	62-002	62-612	62-905



### 8100-Series

Bearing Type: Flat-face  
Contact Diameter: 1.71" - 2.83" (43.4mm - 71.9mm)

Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-8100	1.79" (45.5mm)	62-618	62-6100	62-905



### 8200-Series

Bearing Type: Radius-face  
Contact Diameter: 1.75" (44mm)

Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-8200	1.87" (47.5mm)	62-031	62-6000	62-905
60-8210	1.97" (50.0mm)	62-031	62-6001	62-905
60-8220	2.07" (52.3mm)	62-031	62-6002	62-905
60-8230	2.17" (55.1mm)	62-031	62-6003	62-905
60-8240	2.27" (57.7mm)	62-031	62-6004	62-905
60-8250	2.37" (60.2mm)	62-031	62-6005	62-905
60-8260	2.47" (62.7mm)	62-031	62-6006	62-905
60-8270	2.57" (65.3mm)	62-031	62-6007	62-905
60-8280	2.67" (67.8mm)	62-031	62-6008	62-905
60-8290	2.77" (70.4mm)	62-031	62-6009	62-905

\*Height can be reduced by .050" (1.27mm) by removing the shim that is located under bearing within the piston



### 8300-Series

Bearing Type: Radius-face  
Contact Diameter: 1.50" (38mm)

Part Number	Height*	Replacement Bearing	Replacement Piston	Seal Kit
60-8300	1.87" (47.5mm)	62-008	62-6000	62-905
60-8310	1.97" (50.0mm)	62-008	62-6001	62-905
60-8320	2.07" (52.3mm)	62-008	62-6002	62-905
60-8330	2.17" (55.1mm)	62-008	62-6003	62-905
60-8340	2.27" (57.7mm)	62-008	62-6004	62-905
60-8350	2.37" (60.2mm)	62-008	62-6005	62-905
60-8360	2.47" (62.7mm)	62-008	62-6006	62-905
60-8370	2.57" (65.3mm)	62-008	62-6007	62-905
60-8380	2.67" (67.8mm)	62-008	62-6008	62-905
60-8390	2.77" (70.4mm)	62-008	62-6009	62-905

\*Height can be reduced by .050" (1.27mm) by removing the shim that is located under bearing within the piston

## Features

- **Mount Type:** 2-Bolt pattern
- **Piston Area:** 1.215in<sup>2</sup> (784mm<sup>2</sup>)
- **Max Stroke:** .600" (15.24mm)
- **Ports:** AN3 (3/8"-24 thread)
- **Weight:** .70 - .95 lbs (varies by model)

