

Metallic Clutch Bolt Kits

	Clutch Diameter	Plate Count	Flywheel	Mounting Hole	Size	Length	Length	Part Number
	(inches)	(number)	(type)	(type)	(inches)	(under head)	(grip)	
5.5" Clutches	5.5"	1	Step	Through	5/16"-24	1.72"	1.19"	95-001-5
	5.5"	1	Step	Threaded	5/16"-24	1.47"	.938"	95-015
	5.5"	2	Step/Pot	Through	5/16"-24	1.97"	1.44"	95-002-5
	5.5"	2	Step	Threaded	5/16"-24	1.84"	1.31"	95-009-5
	5.5"	2	Pot	Threaded	5/16"-24	1.72"	1.19"	95-010-5
	5.5"	3	Step	Through	5/16"-24	2.34"	1.81"	95-019
	5.5"	3	Pot	Through	5/16"-24	2.22"	1.69"	95-003-5
	5.5"	3	Step	Threaded	5/16"-24	2.09"	1.56"	95-018
	5.5"	3	Pot	Threaded	5/16"-24	1.97"	1.44"	95-002-5
	5.5"	4	Step	Through	5/16"-24	2.59"	2.06"	95-004-5
	5.5"	4	Pot	Through	5/16"-24	2.47"	1.94"	95-061
	5.5"	4	Step	Threaded	5/16"-24	2.34"	1.81"	95-019
	5.5"	4	Pot	Threaded	5/16"-24	2.22"	1.69"	95-003-5

7.25" Clutches	7.25"	1	Step	Through	5/16"-24	1.47"	.938"	95-026
	7.25"	1	Step	Threaded	5/16"-24	1.34"	.813"	95-009
	7.25"	2	Step	Through	5/16"-24	1.84"	1.31"	95-017
	7.25"	2	Pot	Through	5/16"-24	1.72"	1.19"	95-005
	7.25"	2	Step	Threaded	5/16"-24	1.59"	1.06"	95-028
	7.25"	2	Pot	Threaded	5/16"-24	1.47"	.938"	95-010
	7.25"	3	Step	Through	5/16"-24	2.09"	1.56"	95-018
	7.25"	3	Pot	Through	5/16"-24	1.97"	1.44"	95-006
	7.25"	3	Step	Threaded	5/16"-24	1.84"	1.31"	95-011
	7.25"	3	Pot	Threaded	5/16"-24	1.72"	1.19"	95-014
	7.25"	4	Step	Through	5/16"-24	2.34"	1.81"	95-008
	7.25"	4	Pot	Through	5/16"-24	2.22"	1.69"	95-003-5
	7.25"	4	Step/Pot	Threaded	5/16"-24	2.09"	1.56"	95-012

Cerametallic Clutch Bolt Kits

	Clutch Diameter	Plate Count	Flywheel	Mounting Hole	Size	Length	Length	Part Numbers
	(inches)	(number)	(type)	(type)	(inches)	(under head)	(grip)	
7.25" Clutches	7.25"	1	Step	Through	5/16"-24	1.59"	1.06"	95-028
	7.25"	1	Step	Threaded	5/16"-24	1.47"	.938"	95-010
	7.25"	2	Step	Through	5/16"-24	2.09"	1.56"	95-018
	7.25"	2	Step	Threaded	5/16"-24	1.84"	1.31"	95-011

Note for all bolt kits:

Step-type Flywheel: Clutch friction surface is .100" above clutch mounting surface.


Pot-type Flywheel: Clutch friction surface is equal to clutch mounting surface.



Carbon/Carbon Clutch Bolt Kits

	Clutch Diameter	Plate Count	Flywheel	Mounting Hole	Size	Length	Length	Part Numbers
	(inches)	(number)	(type)	(type)	(inches)	(under head)	(grip)	
5.5" Clutches	5.5"	1	Step/Pot	Through	5/16"-24	1.72"	1.19"	95-001-5
	5.5"	1	Step	Threaded	5/16"-24	1.59"	1.06"	95-029
	5.5"	1	Pot	Threaded	5/16"-24	1.47"	.938"	95-015
	5.5"	2	Step	Through	5/16"-24	2.09"	1.56"	95-018
	5.5"	2	Pot	Through	5/16"-24	1.97"	1.44"	95-002-5
	5.5"	2	Step	Threaded	5/16"-24	1.84"	1.31"	95-009-5
	5.5"	2	Pot	Threaded	5/16"-24	1.72"	1.19"	95-010-5
	5.5"	3	Step	Through	5/16"-24	2.47"	1.94"	95-061
	5.5"	3	Pot	Through	5/16"-24	2.34"	1.81"	95-019
	5.5"	3	Step	Threaded	5/16"-24	2.22"	1.69"	95-003-5
	5.5"	3	Pot	Threaded	5/16"-24	2.09"	1.56"	95-018
	5.5"	4	Step	Through	5/16"-24	2.72"	2.19"	95-060
	5.5"	4	Pot	Through	5/16"-24	2.59"	2.06"	95-004-5
	5.5"	4	Step	Threaded	5/16"-24	2.47"	1.94"	95-061
	5.5"	4	Pot	Threaded	5/16"-24	2.34"	1.81"	95-019


7.25" Clutches	7.25"	1	Step/Pot	Through	5/16"-24	1.72"	1.19"	95-020
	7.25"	1	Step/Pot	Threaded	5/16"-24	1.47"	.938"	95-041
	7.25"	2	Step	Through	5/16"-24	2.09"	1.56"	95-027
	7.25"	2	Pot	Through	5/16"-24	1.97"	1.44"	95-023
	7.25"	2	Step/Pot	Threaded	5/16"-24	1.84"	1.31"	95-063
	7.25"	3	Step/Pot	Through	5/16"-24	2.47"	1.94"	95-016
	7.25"	3	Step/Pot	Threaded	5/16"-24	2.22"	1.69"	95-025
	7.25"	4	Pot	Through	5/16"-24	2.84"	2.31"	95-065
	7.25"	4	Step	Threaded	5/16"-24	2.72"	2.19"	95-064
	7.25"	4	Pot	Threaded	5/16"-24	2.59"	2.06"	95-042



Flywheel Bolt Kits

Bolt kit for mounting Tilton flywheels to the engine crank shaft.

Size	Length	Socket Size	Bolts in Kit	Part Numbers
(inches)	(under head)	(inches)	(number)	
7/16"-20	.875"	1/2" 12-pt	6	95-952-6
7/16"-20	.875"	1/2" 12-pt	8	95-952-8
7/16"-20	.800"	3/4" 12-pt	6	95-975-6
7/16"-20	.800"	3/4" 12-pt	8	95-975-8
11mm x 1.5	.880"	1/2" 12-pt	6	95-940-6



Clutch-to-Flywheel Stud Kits

Clutch-to-Flywheel Stud Kits are designed to press fit into specific Tilton flywheels, such as the 110-tooth flywheel supplied in 52-Series 7.25" Rear-mount Starter Packages.

Clutch Diameter	Plate Count	Part Numbers
(inches)	(number)	
7.25"	3	95-100-6
7.25"	2	95-101-6